

## WILLEMIN MACODEL W 508 MT

**Kind : Turn-mill center**  
**Manufacturer : WILLEMIN MACODEL**  
**Model : W 508 MT**  
**Year : 2007**  
**Serial : 104**  
**Stock : 10495**



### TECHNICAL DETAILS

- Number of axes	: 5
- Number of spindles	: 2
<b>MAIN SPINDLE</b>	
- Spindle speeds	: 6000 [rpm]
- Max. bar diameter	: 42 [mm]
- C axis indexing precision	: 0.0001 [°]
<b>COUNTER-SPINDLE</b>	
- Spindle speeds	: 6000 [rpm]
- Max. bar diameter	: 42 [mm]
<b>CLAMPING DEVICE</b>	
- 2 Jaws chuck	
- Pneumatic clamping	
<b>TURNING-MILLING SPINDLE</b>	
- X/Z stroke	: 450/425 [mm]
- Y stroke	: 200 [mm]
- B Axis stroke	: -15/+100 [°]
- B axis indexing precision	: 0.0001 [°]
- Tool type	: HSK-E40
- Spindle speeds	: 30000 [rpm]
- Spindle power	: 10/15 [kW]
<b>TOOL CHANGER</b>	
- Auto. Tool Changer type	: Bras chargeur
- Tool magazine capacity	: 48
<b>POWER SUPPLY</b>	
- Supply voltage	: 400 [V]

**Kind : Turn-mill center**  
**Manufacturer : WILLEMIN MACODEL**  
**Model : W 508 MT**  
**Year : 2007**  
**Serial : 104**  
**Stock : 10495**

- Total installed power : 35 [kVA]  
**WEIGHT & DIMENSIONS**  
- Machine floor space : 3150 X 2650 [mm]  
- Machine height : 2600 [mm]  
- Machine weight : 2500 [kg]  
**MACHINE HOURS**  
- Number of working hours : 28423 [h]

**EQUIPMENT**

- CNC : Fanuc 31i-model A5  
- Interactive programming  
- 3 colors status lamp  
- Coolant tank  
- Tailstock option with counterspindle  
- Spindle cooling unit  
- Parts catcher  
- Bar loader : LNS QUICK LOAD SERVO III  
\* NB : working order not guaranteed. To have  
it checked by a qualified organization of the  
buyer.  
- hydraulic Unit